


Aluminium pushrims

Special features


Black hard anodized aluminium



- Very scratch resistant
- 6 splices (392114) with two holes
- Ø19 x 1,25
- Splices can be adjusted +/- 2 mm

Wheel Size	SD fitting distance mm	Fit rim types	Weight g	Fitting	Splice Type	Hard Black anodized
22"	466	DW4 & DW7	195	6 rivnuts	6 rivnuts	32221GH
24"	515	DW2 + DW4 + DW7	210	6 rivnuts	6 rivnuts	32241GH
24"	519	DW4 + DW7	215	6 splices	392114	34240YH
25"	536	DW4 + DW7	220	6 splices	392114	34250YH

Ultralight aluminium



- 6 splices (392108) with one hole
- Ø19 x 0,8 mm
- Splices can be adjusted +/- 2 mm

Wheel Size	SD fitting distance mm	Fit Omobic Rim types	Weight g	Fitting	Silver anodized	Black anodized
20"	429	DW4 & DW7	178	6 splices	342077	342075
22"	466	DW4 & DW7	194	6 splices	342277	342278
24"	512	DW2	211	6 splices	342412	342413
24"	517	DW4 & DW7	212	6 splices	342408	342409
24"	523	SW1	216	6 splices	342416S	342416B
25"	535	DW4 & DW7	221	6 splices	342577	342503
25"	542	SW1	224	6 splices	342516S	342516B